

Specifications

Specifications	
DRIVE WHEELS	Standard: 35.6 cm (14") Solid Optional: 35.6 cm (14") Pneumatic
CASTOR WHEELS	Front: 15.2 cm (6") Solid Rear: 15.2 cm (6") Solid
ANTI-TIP WHEELS	N/A
MAXIMUM SPEED ¹	Up to 9.6 km/h (6 mph) Up to 7.24 km/h (4.5 mph) w/iLevel activated
GROUND CLEARANCE	6.9 cm (2.7") (battery tray)
TURNING RADIUS ²	52.1 cm (20.5")
OVERALL LENGTH ²	82 cm (32.23") without front riggings
BASE WIDTH	62.2 cm (24.4")
SEATING SIZES	
Synergy®/TRU-Balance® 3 Static Seat	Width: 25.4 -55.9 cm (10-22") Depth: 25.4 -55.9 cm (10-22")
TRU-Balance® 3 Power Tilt	Width: 30.5 - 55.9 cm (12-22") Depth: 30.5 - 55.9 cm (12-22")
TRU-Balance® 3 Tilt and iLevel®	Width: 30.5 - 55.9 cm (12-22") Depth: 30.5 - 55.9 cm (12-22")
SEAT-TO-FLOOR HEIGHTS ¹⁰	
Synergy®/TRU-Balance® 3 Static Seat ⁵	41.9 - 47 cm (16.5-18.5")
TRU-Balance® 3 Power Tilt ⁵	44.5 - 49.5 cm (17.5-19.5")
TRU-Balance® 3 Tilt & iLevel® 5	44.5 - 49.5 cm (17.5-19.5")
MANUAL RECLINE 6	Yes
BATTERY SIZE ³	NF-22 (2)
BATTERY WEIGHT ⁷	17.24 kg (38 lbs.) each
AVAILABLE ELECTRONICS 8	120A Q-Logic 3 EX
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	2-Pole, Mid-Wheel 6®
WEIGHT CAPACITY ⁴	136 kg (300 lbs.)
BASE WEIGHT	63 kg (138.6 lbs.)
·	1

- 1) Speed varies with user weight, terrain type, battery charge, battery condition and tyre pressure.
 2) Without front riggings
- 3) Battery capacity may change when adding power positioning systems.
- 4) Weight capacity is dictated by the selection of seating.
- 7. High capacity is disclared by the Selection of secting.
 5. All measurements +/-3 mm (1/8") with 46 x 46 c m (18" x 18") seat, fixed towers, 136 kg (300 lbs.) weight capacity and solid tires (add 10 mm (3/8") with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.
 6) Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
 7) Battery weight may vary +/- 1.4 kg (3 lbs.) based on manufacturer.

- 8) All Quantum Rehab® units can be ordered with specialty controls.
- 9) Call for availability
- 10) 41.9 cm (16.5") seat-to-floor height is not available with power tilt or iLevel®. 49.5 cm (19.5") seat-tofloor height is not available with static seat or power recline


Features

Upgraded SRS (Smooth Ride Suspension)

- Gas-charged monotube shocks with springs mounted in a coil-over assembly for a smooth, comfortable ride and advanced stability
- The comfort of soft springs with the control of real dampening shocks
- All shocks function independently of each other
- Same springs and shocks as the 4Front™
- Close simulation to automative suspension
- 7.24 km/h (4.5 mph) at iLevel[®]
- Fender lights and USB charger
- Bold new colours
- Made in Australia of foreign and domestic parts



7 New Colours* (12 in Total)







MIDNIGHT BLUE

NIGHT TRAIN



