



Narrowest complex rehab base on the market



quantumrehab.com

Specifications

DRIVE WHEELS	35.6cm (14") or 31.8cm (12.5") pneumatic or flat free tires
CASTER WHEELS	Front: 12.7cm (5") flat free Rear: 15.2cm (6") flat free
MAXIMUM SPEED ¹	Up to 10 km/h Up to 5.6 km/h w/iLevel activated
GROUND CLEARANCE	7.4cm (2.9")
TURNING RADIUS ²	53.3cm (21")
OVERALL LENGTH ²	82.5cm (32.5") without front riggings
BASE WIDTH	55.25cm (21.8") with 35.6cm (14") drive wheels 52.71cm (20.8") with 31.8cm (12.5") drive wheels
SEATING SIZES	
TRU-Balance® 3 Static Seat	Width: 12"W-16"W Depth: 12"W-16"W
TRU-Balance® 3 Power Tilt	Width: 12"W-16"W Depth: 12"W-16"W
TRU-Balance® 3 Tilt and iLevel®	Width: 12"W-15"W OR 15"W-16"W Depth: 12"D-16"D OR 16"D-20"D
SEAT-TO-FLOOR HEIGHTS	
TRU-Balance® 3 Static Seat ⁵	40.6cm (16")-45.7cm (18")
TRU-Balance® 3 Power Tilt ⁵	44.5cm (17.5")-49.5cm (19.5")
TRU-Balance® 3 Tilt & iLevel® 5	44.5cm (17.5")-49.5cm (19.5")
MANUAL RECLINE 6	Yes (TRU-Balance® Flex only)
BATTERY SIZE ³	40 AH (2) or 55 AH (2)
BATTERY WEIGHT ⁷	40 AH: 14 kg each 55 AH: 18.1 kg each
AVAILABLE ELECTRONICS 8	120A Q-Logic 3 EX
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	2-Pole, Mid-Wheel 6®
WEIGHT CAPACITY ⁴	136 kg
BASE WEIGHT WITHOUT SEATING SYSTEM	57.3 kg

- 1) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
- 2) Without front riggings
- 3) Battery capacity may change when adding power positioning systems.
 4) Weight capacity is dictated by the selection of seating.
- 5) All measurements +/- 0.3cm (0.1") with 45.7cm (18") x 45.7cm (18") seat, fixed towers, 136 kg weight capacity and solid tires (add 0.95cm (0.4") with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system
- 6) Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
- 7) Battery weight may vary +/- 1.4 kg based on manufacturer.
- 8) All Quantum Rehab® units can be ordered with specialty controls.
- 9) Call for availability.

Features

- Independent SRS (Smooth Ride Suspension)
- iLevel® option available with up to 30.5cm (12") of seat elevation at walking speed (up to 5.6 km/h)
- Fender lights and USB charger included
- Assembled in Australia of foreign and domestic parts
- WC 19 Occupied transit approved

Options

- iLevel® option allows 30.5cm (12") of seat elevation while at walking speed (5.6 km/h)
- Q-Logic 3 EX Drive Controls
- TRU-Balance® 3 Seating
- Trilogy vent tray⁹
- Compact vent tray9
- 30.5cm (12") x 30.5cm (12") seat sizes with iLevel (SOF only)

Colours*





